



Producto : Selector M-O-A
Marca : Timax
Modelo : TM16-61025
Amps : 16A
Polos : 1 P – 2P
Certificac. :



AC Rating Code	Unit	S16/TP16/ RT16
Rated Operational Voltage (UE)	V	690
Rated frequency	Hz	50/60
Rated impulse withstand Voltage (Uimp)	Kv	6
Rated Operational Current (Ie) AC21/AC1	A	16
Rated Uninterrupted Current (Ith)	A	20
Rated Operational Power		
AC23A "3 Ph, 415 V"	KW	7.5
	A	13
AC3	KW	5.5
"3 Ph, 415 V"	A	10
Short Circuit Capacity		
Rated Fuse Short Circuit Current	KA	5
Fuse Size (Type Gg/Gm)	A	16
Terminal Cross Section		
Single / Multiple	min	mm2 1.5
	max	mm2 4
Fine strand	min	mm2 1
	max	mm2 2.5
Terminal Cross Section	Metric	M3.5
terminal Tightening Torque	Nm	0.8

CSA/UL Ratings

AC Rating Code	Unit	S16/TP1 6/RT16
Ampere Rating	A	15
Operational Voltage	V	600
HP Rating 1 Phase 120V	HP	0.33
240V	HP	1
3 Phase 120V	HP	1.5
240V	HP	3
480V	HP	3
600V	HP	5

